8 □□□□ □□□□□□□ □□□□□□□□□ □□□□□□□□□ □□□□□ □□□ □□□□□□□□□□□□

□□□□□ □□□□□□□ □□□□□□□□□ □□□□□□ □□□ □□□□ □□□□□ □□□, □□□□□□□□□ □□□□ □□□□ □□□□ □□□□, □□□□ □□□□□□□ □□□ □□□□ □□□□ □□□□ □□□□□□□□, □□□□□□□□□ □□□□ □□□□□□□□ □□□□□□□□ □□□□□□ □□□ □□□ □□□□□□□□□□□□□□ □□□ □□□□□□□ □□□ □□□□□□

KXG □□□□□ □□□□□□ □□□□□□□ □□□□□□□□ □□□□□, □□□□□□□□-□□□□□ □□ □□□□□□□□□□ □□□□ □□□ □□□ □□□□□ 8 □□□□ □□□□□□□□□ □□□□□ □□□□ □□□ □□□□□□□□□ □□□□□, □□□□□□□□□□□□□□ □□□□□□□ □□□□□□□□□ □□□□□, □□□ □□□□□□□□□ □□□□□□□□□ □□□□□, □□□□□-□□□□□□□ □□□□□□□□□□ □□□□□□□□□ □□□□□ □□□□□□□

• □□□□ □□□□□: 8 □□□□ □□□□□□□□□ □□□ 8 □□□□ □□□□□□ □□□□□□□□□□□□□□ □□□□ 3-5 □□□ □□□□□□□□□, □□□□ □□□□□□ □□□ □□, □□□□ □□□ □□□□ □□□□ □□□□

• □□□□□□ □□□□□□: □□ □□□□□ □□□□ - 3000 * 8000 □□□□ □□□□, □□ □□□□□ □□□□ - □□ □□□□□ □□□□□□□□□ □□□□ □□□□□□□, □□□□□□□□, □□□□□□□□□□□, □□□□□□□□□□ □□□□□□□ - □□□□□□□, □□□□□□, □□□□□ □□□□□□□ □□□□□□□□

• □□□□ □□□□□□□: □□□ 8 □□□□ □□□□□□□□□ □□□□□ □□□□ □□□ □□□ □□□ □□□□ □□□□ □□□ □□□ □□□, □□ □□□□□□□□□ □□□□ □□□□□□□□□ □□□

Ason □□□□□□□□□□□ □□□□: 8 □□□□ □□□□□□□□□ □□□□ □□□□□□ □□□□□ □□□□ □□□□ □□ □□□ □□□□□□ □□□□□

Feature(性能)	Tempered(钢化)	Heat strengthened(半钢化)	Normal(普通)
Safety(安全性)	best(最好)	general(一般)	none(没有)
Intensity(强度)	150mpa	100~1520mpa	30~90mpa
Themal stabilityre(热稳定性)	250~320℃	100℃	2~100℃
Surface stress(表面应力)	95mpa	24-69mpa	……
Broken state(破碎状态)	obtuse-angele grain(纯角颗粒)	shooting broken(放射状破碎)	sharp(锐利)
Self- destruction(自爆)	sometimes(会)	seldom(基本不会)	never(不会)

[illegible] KXG [illegible]

• [illegible]-[illegible], [illegible],

Ful [illegible], [illegible]

• [illegible], [illegible], [illegible], [illegible], ISO [illegible], ANSI [illegible]

Delivery [illegible], 1000 [illegible], 7 [illegible]