



KXG 玻璃产品性能参数表											
玻璃类型	厚度	透光率 (%)	反射率 (%)	透射率 (%)	吸收率 (%)	折射率	热膨胀系数 (1/°C)	RHG	重量 (kg/m²)	抗冲击强度 (kJ/m²)	抗弯强度 (N/mm²)
普通玻璃	5mm	51,94%	6,44%	14,52%	51,78%	6,69%	62,50%	0.70	0.84	5.64	5,272
	6mm	47,15%	6,73%	11,83%	46,87%	6,79%	58,83%	0.66	0.83	5.606	5,243
钢化玻璃	5mm	51,66%	6,36%	20,29%	49,19%	6,48%	60,63%	0.68	0.84	5.623	5,272
	6mm	45,24%	6,06%	16,47%	42,98%	6,15%	56,11%	0.63	0.84	5.582	5,243
夹胶玻璃	5mm	47,90%	6,77%	19,87%	46,96%	6,75%	58,91%	0.66	0.84	5.606	5,272
	6mm	41,96%	6,59%	16,54%	41,37%	6,53%	54,82%	0.62	0.83	5.569	5,243
中空玻璃	5mm	71,07%	7,78%	26,60%	53,99%	6,94%	64,07%	0.72	0,654	5,272	5,843
	6mm	67,74%	7,69%	24,13%	50,67%	6,96%	61,61%	0.69	0,632	5,243	5,808
镀膜玻璃	5mm	74,60%	8,03%	24,54%	48,75%	6,67%	60,26%	0.68	0,619	5,272	5,843
	6mm	71,36%	7,66%	20,22%	43,72%	6,35%	56,60%	0.64	0,586	5,243	5,808

