

**6 AAA + 9A + 8 mm** **IGU** **23 mm** **IGU**



**6 mm + 12A + 6 mm** **IGU**

6 mm + 12A + 6 mm IGU is a double-pane glass unit with a 12mm air gap. It is commonly used for thermal insulation in buildings. The glass thickness is 6mm, and the air gap is 12mm. The total thickness of the unit is 24mm. It is often used in conjunction with a 23mm IGU for enhanced thermal performance. The unit is typically used in double-pane glass doors and windows. The unit is often used in conjunction with a 23mm IGU for enhanced thermal performance. The unit is typically used in double-pane glass doors and windows.



本公司生產之玻璃，係採用最優良之原料，經科學方法精製而成。其品質優良，堅固耐用，且具優良之透光率。本公司之玻璃，均經嚴格之品質檢驗，確保其品質優良。本公司之玻璃，均採用最優良之原料，經科學方法精製而成。其品質優良，堅固耐用，且具優良之透光率。本公司之玻璃，均經嚴格之品質檢驗，確保其品質優良。



**6 AAA + 9A + 8 mm 鋼化玻璃 產品規格：**

- 鋼化，鋼化，鋼化，鋼化 鋼化玻璃
- 鋼化玻璃 鋼化玻璃，
- 鋼化玻璃 鋼化玻璃 鋼化玻璃，鋼化玻璃 鋼化玻璃
- 鋼化，鋼化玻璃，鋼化玻璃，鋼化玻璃，鋼化玻璃，鋼化玻璃 鋼化玻璃 鋼化玻璃 鋼化玻璃 鋼化玻璃 鋼化玻璃。
- 鋼化玻璃。



**KXG 鋼化玻璃 產品規格**

本公司生產之鋼化玻璃，係採用最優良之原料，經科學方法精製而成。其品質優良，堅固耐用，且具優良之透光率。本公司之鋼化玻璃，均經嚴格之品質檢驗，確保其品質優良。

規格：鋼化玻璃：2500 mm \* 4000 mm, 鋼化玻璃：180 mm \* 350 mm.

Spacer: 3 mm or 19 mm.

Spacer: 3 mm, 6 mm, 9 mm, 12 mm, 16 mm, 19 mm.

Spacer: 3 mm, 6 mm, 9 mm, 12 mm, 16 mm, 19 mm, 25 mm, 32 mm, 38 mm, 45 mm, 51 mm, 57 mm, 63 mm, 69 mm, 75 mm, 81 mm, 87 mm, 93 mm, 99 mm, 105 mm, 111 mm, 117 mm, 123 mm, 129 mm, 135 mm, 141 mm, 147 mm, 153 mm, 159 mm, 165 mm, 171 mm, 177 mm, 183 mm, 189 mm, 195 mm, 201 mm, 207 mm, 213 mm, 219 mm, 225 mm, 231 mm, 237 mm, 243 mm, 249 mm, 255 mm, 261 mm, 267 mm, 273 mm, 279 mm, 285 mm, 291 mm, 297 mm, 303 mm, 309 mm, 315 mm, 321 mm, 327 mm, 333 mm, 339 mm, 345 mm, 351 mm, 357 mm, 363 mm, 369 mm, 375 mm, 381 mm, 387 mm, 393 mm, 399 mm, 405 mm, 411 mm, 417 mm, 423 mm, 429 mm, 435 mm, 441 mm, 447 mm, 453 mm, 459 mm, 465 mm, 471 mm, 477 mm, 483 mm, 489 mm, 495 mm, 501 mm, 507 mm, 513 mm, 519 mm, 525 mm, 531 mm, 537 mm, 543 mm, 549 mm, 555 mm, 561 mm, 567 mm, 573 mm, 579 mm, 585 mm, 591 mm, 597 mm, 603 mm, 609 mm, 615 mm, 621 mm, 627 mm, 633 mm, 639 mm, 645 mm, 651 mm, 657 mm, 663 mm, 669 mm, 675 mm, 681 mm, 687 mm, 693 mm, 699 mm, 705 mm, 711 mm, 717 mm, 723 mm, 729 mm, 735 mm, 741 mm, 747 mm, 753 mm, 759 mm, 765 mm, 771 mm, 777 mm, 783 mm, 789 mm, 795 mm, 801 mm, 807 mm, 813 mm, 819 mm, 825 mm, 831 mm, 837 mm, 843 mm, 849 mm, 855 mm, 861 mm, 867 mm, 873 mm, 879 mm, 885 mm, 891 mm, 897 mm, 903 mm, 909 mm, 915 mm, 921 mm, 927 mm, 933 mm, 939 mm, 945 mm, 951 mm, 957 mm, 963 mm, 969 mm, 975 mm, 981 mm, 987 mm, 993 mm, 999 mm.

Spacer: 6, 9, 12, 16 mm (1/4", 11/32", 1/2", 5/8").

Spacer Fill: Dry Dry, 3 mm, 6 mm, 9 mm, 12 mm, 16 mm, 19 mm.

Spacer: 3 mm, 6 mm, 9 mm, 12 mm, 16 mm, 19 mm.

### **KXG 6 mm + 9A + 8 mm** spacer glass panel assembly



### **KXG 6 mm + 9A + 8 mm** spacer glass panel assembly

