5mm 6mm black tinted dark grey color tempered glass panel

5mm 6mm black tempered glass, also known as dark gray tempered glass, dark grey toughened glass, 5mm 6mm black energy-savingtempered safety glass, 5mm 6mm black heat-absorbing tempered glass, 5mm 6mm dark gray decorative stained glass, processed high quality 5mm dark gray glass 6mm dark grey tinted float glass. It not only retains the advantages of darkgrey tinted glass, but is also one of the safest glasses. Widely used as window glass, cabinet door glass, kitchen splash glass



Advantages of Kunxing glass tempered glass

- Hardness: 5mm 6mm black temperedglass is 3 to 5 times harder than 5mm 6mm black colored glass.
- UV-resistant, heat-resistant: 5 mm 6 mm black tempered glass, with anti-ultraviolet and heat-reducing functions, can be made into 5 + 5 mm 5 + 6 mm 6 + 6 mm hollow glass as a curtain wall toprotect furniture from fading and reduce solar glare and heat transfer. It is energy-saving glass.
- Safety: It is a safety glass that plits into tiny, harmless items when it is destroyed by external forces.
- Special signs and patterns can be printed on tempered glass.
- Excellent resistance to thermalstress and wind load.



| Color | Thickness | Visible Light Transmittance | Visible Light Reflectance | UV Light Transmittance | Direct Sinlight Transmittance | Direct Sunlight Reflectance | Total Solar Transmittance | Shading Coeffcient (SC) | RHG | K Value (Summer Daytime) | K Value (Winter Night) |
|-------------|-----------|--------------------------------|------------------------------|---------------------------|-------------------------------------|-----------------------------------|------------------------------|-------------------------------|--------|--------------------------------|---------------------------|
| Euro Bronze | 5mm | 51. 94% | 6. 44% | 14. 52% | 51.78% | 6. 69% | 62. 50% | 0.70 | 0.84 | 5. 64 | 5, 272 |
| | 6mm | 47. 15% | 6. 73% | 11. 83% | 46. 87% | 6. 79% | 58. 83% | 0.66 | 0.83 | 5. 606 | 5. 243 |
| Euro Grey | 5mm | 51. 66% | 6. 36% | 20. 29% | 49. 19% | 6. 48% | 60. 63% | 0.68 | 0.84 | 5. 623 | 5. 272 |
| | 6mm | 45. 24% | 6.06% | 16. 47% | 42. 98% | 6. 15% | 56. 11% | 0.63 | 0.84 | 5. 582 | 5. 243 |
| Dark Grey | 5mm | 47. 90% | 6. 77% | 19.87% | 46, 96% | 6. 75% | 58.91% | 0. 66 | 0.84 | 5. 606 | 5. 272 |
| | 6mm | 41.96% | 6, 59% | 16, 54% | 41.37% | 6, 53% | 54. 82% | 0. 62 | 0.83 | 5, 569 | 5. 243 |
| Light Blue | 5mm | 71. 07% | 7. 78% | 26. 60% | 53, 99% | 6. 94% | 64. 07% | 0.72 | 0. 654 | 5. 272 | 5. 843 |
| | 6mm | 67. 74% | 7. 69% | 24. 13% | 50. 67% | 6. 96% | 61.61% | 0. 69 | 0. 632 | 5. 243 | 5. 808 |
| F-Green | 5mm | 74. 60% | 8. 03% | 24. 54% | 48. 75% | 6. 67% | 60. 26% | 0.68 | 0. 619 | 5. 272 | 5. 843 |
| | 6mm | 71. 36% | 7. 66% | 20. 22% | 43. 72% | 6. 35% | 56. 60% | 0.64 | 0. 586 | 5. 243 | 5. 808 |

For reference only

5mm 6mm dark gray tempered glass features

- 1. Thickness: 5mm 6mm
- 2. Size: The largest size is 2440 * 3660mm,can be customized according to customer requirements
- 3. Special processing: drilling, cutting,marking printing, polishing edges, etc. need to be completed before tempering. It is a perfect dark grey tempered <u>laminated glass</u> with dark grey tempered insulating glass.

Application of 5mm 6mm dark gray tempered glass

- 1. glass shelf, glass cutting board, glass table top, glass splash board
- 2. railings, windows, doors, <u>curtain walls</u>

Tinted glass package in KXG











