



Feature(性能)	Tempered(钢化)	Heat strengthened(半钢化)	Normal(普通)
Safety(安全性)	best(最好)	general(一般)	none(没有)
Intensity(强度)	150mpa	100~1520mpa	30~90mpa
Thermal stability(热稳定性)	250~320℃	100℃	2~100℃
Surface stress(表面应力)	95mpa	24~69mpa	.....
Broken state(破碎状态)	obtuse-angle grain(纯角颗粒)	shooting broken(放射状破碎)	sharp(锐利)
Self-destruction(自爆)	sometimes(会)	seldom(基本不会)	never(不会)

XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX **Kunxing** XXXXXXXXXXXXXXXXXXXX XXXXXXXXXXXXXXXXXXXX

XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX  
 XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX  
 XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX  
 XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX  
 XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX  
 XXXXXXXXXXXXXXXXXXXXXXX (XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX)  
 XXXXXXXXXXXXXXXXXXXXXXX  
 XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX etching  
 XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX  
 XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX

XXXXXXXXXXXX XXXXXXXX XXXXXXXX XXXXXXXX **KXG**



