

XX, XX XX X X XX.XX XX XX
XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX

XXXXXXXX XX.XX XX XX XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX

XX.XX XX XXX [XXXXXXXXXXXXXX.XX XXXXXXXXXXXXXXX](#)
XX XX.XX XX XX XX XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX
XX XXX
XX XXX
XX XXX



XX
[XXXXXXXXXXXXXXXXXXXX](#)

interlayer

Ultra Clear Glass / Low iron Glass Specification

Thickness (mm)	Weight (KG/SQM)	Visible light %		Solar Radiant Heat %				Shading Coefficient (SC)	U Valve (W/SQM)	Sound-Proofing
		Transmission	Reflectivity	Direct Penetrate	Reflectivity	Absorb	Total Penetrate			
3	7.5	91.6	8	90	8	1	91	1.05	5.8	30
4	10.0	91.4	8	90	8	2	91	1.05	5.8	30
5	12.5	91.3	8	90	8	2	90	1.03	5.8	32
6	15.0	91.1	8	89	8	3	90	1.03	5.7	32
8	20.0	91.0	8	88	8	4	89	1.02	5.7	34
10	25.0	90.6	8	88	8	4	89	1.02	5.6	36
12	30.0	90.4	8	87	8	5	88	1.01	5.5	37
15	37.5	90.1	8	86	8	6	87	1.00	5.5	38
19	47.5	89.7	8	84	8	7	86	0.99	5.5	40
22	55.0	89.6	8	82	8	9	85	0.97	5.5	43
25	62.5	89.0	8	81	8	9	84	0.95	5.5	45



