

12

12

12

12 600 ° C



12

12

- 1.
- 2.
- 3.
- 4.
- 5.
- 6.
- 7.

Feature(性能)	Tempered(钢化)	Heat strengthened(半钢化)	Normal(普通)
Safety(安全性)	best(最好)	general(一般)	none(没有)
Intensity(强度)	150mpa	100~1520mpa	30~90mpa
Thermal stability(热稳定性)	250~320℃	100℃	2~100℃
Surface stress(表面应力)	95mpa	24~69mpa
Broken state(破碎状态)	obtuse-angle grain(纯角颗粒)	shooting broken(放射状破碎)	sharp(锐利)
Self-destruction(自爆)	sometimes(会)	seldom(基本不会)	never(不会)

XXXXXXXXXXXXXXXXXXXXXXXXXXXX **Kunxing** XXXXXXXXXXXXXXX

XXXXXXXXXXXXXXXXXXXXXXXXXXXX
 XXXXXXXXXXXXXXXXXXXXXXXXXXXX
 XXXXXXXXXXXXXXXXXXXXXXXXXXXX
 XXXXXXXXXXXXXXX
 XXXXXXXXXXXXXXXXXXXXXXX
 XXXXXXXXXXXXXXX (XXXX, XXXXXX, XXX, XXXXXXX, XXXXXXXXXXX)
 XXXXXXXXXXXXXXXXXXXXXXX
 XXXXXXXXXXXXXXXXXXXXXXX
 XXXXXXXXXXXXXXXXXXXXXXX
 XXXXXXXXXXXXXXXXXXXXXXX

XXXXXXXX XXXXXX XXXXXXXXXXXXXXX **KXG**



