[illegible] 12 [illegible]. [illegible]

[illegible]



[illegible]

1. [illegible]

2. [illegible]: [illegible]

3. [illegible]

[illegible] 12 [illegible]. [illegible]

[illegible]: 12mm [illegible] [[illegible]]() [illegible] 12 [illegible]. [illegible]

[illegible]: [illegible] 12 [illegible]. [illegible], [illegible] 12 [illegible]. [illegible], [illegible] 12 [illegible]. [illegible], 12mm [illegible], [illegible] 12 [illegible]. [illegible], [illegible]

Products name 产品名称	CurvedTemperedglass 弯钢化玻璃
Thickness 厚度	4-19mm
Maximum size 最大尺寸	2440mmX8000mm
Minimum Radius Range 最小弯钢半径	5-6mm R>=450mm; 8mm-10mm R>=650mm; 12mm-19mm R>=1200
Features 特性	It has same safety and ability of anti-impact with flat tempered glass, but has a higher intensity for the wind pressure and bending than the flat tempered glass.
Certification 认证资质	CCC, ISO, CE, AS/NZS2208

[illegible]

[illegible]: [illegible] [illegible] 12 [illegible]. [illegible] [illegible]

[illegible]: [illegible] 12mm [illegible] 12 [illegible]. [illegible] 12 [illegible]. [illegible] 4-5 [illegible]

[illegible]: 3300x18000mm [illegible] [illegible] [illegible]

[illegible]: [illegible], [illegible], [illegible] [illegible]

[illegible] KXG LASS

--- [illegible] 8 [illegible] 10 [illegible] temperedglass [illegible] [illegible] 12 [illegible]. [illegible] 12 [illegible]. [illegible]

---[illegible] [illegible] 4 + 9a + 4mm, [illegible] 5 + 9a + 5mm, [illegible] 6 + 12a + 6mm

- [illegible] 4 + 4 [illegible]., [illegible] 5 + 5 [illegible]., [illegible] 6 + 6 [illegible]., [illegible], [illegible], [illegible] [illegible] [illegible] [illegible]